

2013 Truck Specifications

Compliance		Specifications
Item #	Yes	No
		Chassis- Single axle construction dump
1		Single- Heavy Duty Frame Rails Front rail extension (plow upfit)
1a.		Manufacture frame rail size:
1b.		Cab to axle range 90" to 104.2
2		Hot bolt cross members
		Engine
3		Pacar PX9-370 hp (370@2000)
3a.		Engine Brake (2-3 stage) (jacobs replaces turbo exhaust brake)
4		1250 lbs torque @ 1400 rpms
5		Exhaust Single- RH side of Cab curved tip Chrome
6		On/off clutch fan
7		Preheater 110-120v
8		160 amp alternator
9		High efficiency cooling system
10		Spin on fuel filters- frame mounted
11		2-Batteries 1800 CCA - with battery jumper terminals
		Suspension
12		Front end- 20,000 lb (Dana Spicer D2000)
13		Front Springs- Taperleaf 20K, with shock absorbers.
14		Front End - Bendix Air Cam drum brakes for 20K-22K, auto slack adjusters
15		Front End- Iron Hub 20K
16		Front End- Power steering cooler
17		Front Wheels: Aluminum 22.5 x9
18		Front Tires: 315/80R22.5 20 ply summer
19		Rear End- Dana Spicer S26-190 rear axle; 26K
20		Rear end- Reyco 79KB 26K steel
21		Rear End- Reyco helper springs 4,500 lbs
22		Rear End- Ration 5.38
23		Rear End- Bendix Air Cam rear drums brakes
24		Rear End- Diff Lock
25		Rear End- Anti Lock braking
26		Rear Wheels: Aluminum 24.5 x 8.25
27		Rear Tires: 12R22.5 16 Ply M&S
28		Spare Rim: Aluminum size TBD
		Air & Trailer Equipment
29		Bendix Air Dryer w/ heater
30		Berg pull cord drain valves- all air tanks
31		Nylon Chassis hose
32		Rear trailer air connections
		Transmission
33		Allison 3000 RDS-P Rugged Duty Series
34		Heavy Duty driveline, w/ center bearing
35		push button 6-sp control
36		Transmission PTO accessory for upfitter.
		Fuel Tanks
37		Minimum 70 gallon diesel tank, driverside step
38		DEF tank, mounted LH behind front fender forward of fuel tank.
		Cab/lighting/Misc
39		Alumimum Cab with fiberglass hood, with hood access panel
40		Air ride driver & passender seats- fabric, highback with lumbar control & Arm Rest
41		Cab Heater/Cab AC and intergal defroster

2013 Truck Specifications

Item #	Yes	No	Specifications
42			Adjustable steering wheel, tilt and telescoping
43			Rubber flooring with floor mats
44			Center console cup holder
45			LH manual window and RH electric
46			Day cab rear window
47			AM/FM/Weather band LED radio
48			Driver/Passenger Red seatbelts replace standard
49			Outside sunvisor, stainless steel
50			Dashboard with gauge clusters
51			Marker lights, and wiring for rear LED lighting to be installed by upfitter. (Junction box in cab)
52			Dual Chrome air horns with caps
53			Chrome grab handles RH& LH
54			RH & LH Mirrors (Heated-switched) (7 x 16)
55			RH & LH Mirrors (Heated-switched) (8" convex- Fender mounted)
56			RH & LH Mirrors (8" heated convex mounted below mirrors)
57			Single Convex mirror - Right hand passenger door - non heated)
58			Daylite Door- RH peeper window
59			Halogen headlamps- upfitter interface- plow headgear
60			CB Radio accessory wiring
61			5lb dry chemical fire extinguisher & DOT Triagle kit
62			Solid Metallic dark green pa+D91it with clearcoat
63			7 pin trailer plug with electric trailer brake controler.
			Warranty
64			Extended Warranty- 5 yr minimum (Engine, Transmission, electronics, turbo etc)
			Plow, wing, combination dump/spreader Upfit equipment Specifications
65			Everest Custom Power Tilt Hitch with DA Lift Cylinder, plow lights, Font Wing Post with slide and trip hinge.
66			Hi-Lift PatrolmWing rear weldment
67			PTO hyd pump, off automatic transmission accessory
68			Sectional Valve for all functions to include cab controls
69			11' Power Angle- highway style (horn) plow- with carbide edge.
70			W132 RH Wing with full trip wing arms and carbide edge
71			CS550 Lite Closed Loop ground speed controls
72			AirFlo 10' - 9.5 yd combination sander body with 24" cab shield
73			Boxed Top rail with vertical side bracing, 7 ga sides with 1/4" floor.
74			ICC lights, reflectors front & rear, front and rear mud flaps
75			Paint: Black gloss
76			Mailhot 20 Ton Hoist w/ safety brace
77			Back-up alarm
78			Bullett electric load cover
79			24 Ton Pintle Hook on 3/4" plate with "D" rings
80			1-Pr Poly fenders