

TOWN OF MOULTONBOROUGH, NEW HAMPSHIRE
6 Holland Street
P.O. Box 139
Moultonborough, NH 03254

**FY2025 10-Wheel Truck with
Dump Body, Plow, Wing, and Sander**

ADDENDUM No.1 – October 25, 2024

Please Note: Addendum No.1 is being issued in response to the following questions:

Questions:

1. Do you want any air horns? *Answer: Yes*
2. Air intake snow doors? *Answer: Yes*
3. Vertical or horizontal exhaust? *Answer: Vertical Exhaust*
4. Transmission secondary shift mode programming to perhaps 3rd gear hold?
Answer: Yes
5. Push button or column stalk shift mechanism? *Answer: Push Button Shift*
6. Brake dust shields? *Answer: No*
7. Premium cab insulation? *Answer: No*
8. Plumbing ball shutoff valves? *Answer: No*
9. Oil temperature gauge? *Answer: Yes*
10. Transmission temperature gauge or maybe a digital transmission oil temperature in the driver display? *Answer: Transmission Temperature Gauge*
11. Double wrap on wiring? *Answer: Yes.*

EXHIBIT A
(Addendum No.1 – October 25, 2024)

Compliance			Current Year Western Star 47X (Set Forward Front Axle Chassis) (or Equal)
			Specifications:
Features	Yes	No	
1			Minimum GVW: 64,000. lbs.
2			DETROIT DD13 Gen 5 12.8L 505 HP @ 1625 RPM, 1900 GOV RPM, 1850 LB/FT @ 975 RPM (or Equal)
3			75 Mph Road Speed Limit Cruise Control Speed Limit Same as Road Speed Limit
4			Trailer Towing Provision at End of Frame for Truck
5			Front Plow/End Dump Body
6			DR 12V 160 AMP 28-SI
7			3-Batteries 2700 CCA Min.- With Battery Jumper Terminals
8			Positive Load Disconnect with Cab Mounted Control Switch with Locking Provision Mounted Outboard Driver Seat
9			Positive and Negative Posts for Jumpstart Located on Frame Next to Starter
10			Minimum 13 Gallon Diesel Exhaust Fluid Tank
11			DDC Supplied Engine Mounted Fuel Filter/Fuel Water Separator with Water-In-Fuel Indicator (Or Equal)
12			1350 Adapter Flange for Front PTO Provision
13			Phillips-Temro 1500 Watt/115 Volt Block Heater (Or Equal)
14			Phillips-Temro 300 Watt/115 Volt Oil Preheater (Or Equal)
15			Engine Heater Receptacle Mounted Under LH Door
16			Allison 4000 RDS Automatic Transmission with PTO Provision (Or Equal)
17			Electronic Transmission Customer Access Connector, Blunt Cut, Mounted Between Driver and Passenger Seats
18			Transmission secondary shift mode programming to 3rd gear hold
19			Push Button Shift Mechanism
20			Detroit DA-F-20.0-5 20,000# FL1 71.0 KPI/3.74 Drop Single Front Axle (or Equal)
21			9,500# Left, 10,500# Right Mixer/Plow Flat Leaf Front Suspension (20,000#) (Or Equal)
22			RT-46-160 46,000# R-Series Tandem Rear Axle (Or Equal)
23			4.56 Rear Axle Ratio
24			Driver Controlled Traction Differential – Both Tandem Rear Axles
25			Automatic Rear Slack Adjusters
26			Hendrickson Haulmaax EX 46,000# Rear Suspension (Or Equal)
27			Air Dryer with Heater
28			WABCO Oil Coalescing Filter For Air Dryer (Or Equal)
29			Steel Air Tanks Mounted Outside And/or Below Frame Just Forward of Rear Suspension
30			Clear Frame Rails from Back of Cab to Front Rear Suspension Bracket, Both Rails Outboard
31			Air Connections to End of Frame with Glad Hands for Truck

32		Primary Connector/Receptacle Wired For Separate Stop/Turn, ABS Center Pin Powered Through Ignition
33		SAE J560 7-Way Primary Trailer Cable Receptacle Mounted End of Frame
34		Double wrap on wiring
35		5640MM (222 Inch) Wheelbase
36		Single- Heavy Duty Frame Rails Front rail extension (plow upfit)
37		70 Gallon/264 Liter Aluminum Fuel Tank - LH
38		11R22.5 16 Ply Radial Rear Tires - 315/80R22.5 20 Ply Radial Front Tires
39		Fiberglass Hood with Access Hatches
40		Air intake snow doors
41		Switch, Indicator Light and Wiring For (2) Customer Furnished Beacons
42		LED Marker Lamps
43		Wiring and Switch for Customer Furnished Snow Plow Lamps with Dual Connections at Bumper
44		Dual Stainless Steel Heated Mirrors
45		LH And RH Sureplus 574 8 Inch Bright Finish Heated Convex Mirrors with Separate Adjustment, Mounted Below Mirror (Or Equal)
46		RH and LH 8 Inch Heated Stainless-Steel Fender Mounted Convex Mirrors with Tripod Brackets (Or Equal)
47		18" Steering Wheel
48		Stainless Steel Exterior Sun Visor
49		Vertical Exhaust
50		RH And LH Electric Powered Windows
51		Lower RH Door Window with Fresnel Lens
52		2-Piece Tinted Curved Gasket Mounted Heated Windshield
53		Charcoal Black Vinyl Premium Interior
54		Black Mats with Double Insulation
55		5 Lb. Fire Extinguisher
56		Air Horns
57		12 Volt Power Supply In-Dash plus 12Volt USB Port
58		Premium High Back Air Suspension Driver Seat With 3 Chamber Air Lumbar, Integrated Cushion Extension, Forward and Rear Cushion Tilt, Adjustable Shock Absorber (Mordura Cloth)
59		Dual Driver Seat Armrests, No Passenger Seat Armrests
60		97 Db Backup Alarm
61		Oil temperature gauge
62		10. Transmission temperature gauge
63		Outside Air Temperature Gauge with Fahrenheit And Celsius Display Mounted in Overhead Console
63a		AM/FM/WB World Tuner Radio with Cd Player, Bluetooth, iPod Interface, USB And Auxiliary Inputs, J1939
63b		Six Ignition Controlled Extra Switches with Indicator Light, 20 Amps, Wired Behind Passenger Seat
63c		Cab Marker Light and Headlight Switch with Separate Switch and Terminals for Customer Furnished Snow Plow Lights and Turn Signals
63d		Cab Color: Solid Metallic Dark Green

63e		Black, High Solids Polyurethane Chassis Paint
63f		Bumper Painted Same as Chassis
63g		Wheels and Rims: Black Powder Coated
63h		Custom Hitch with Mounting Bolts, Nuts, and Pins
63i		Custom Hitch Plow & Wing Mount-Power Tilt (incl. yoke)
64		Access Step
64a		4"x10" DA Cylinder
64b		SAE "C" 2 Bolt Constant Running Pump
65		30 1/2" Push Center
65a		Hose Connecting Bracket w/Restrictor, Fittings and Disconnect
65b		FH20 Hydraulic Assembly w/Mounting Bracket (3 x 20 cyl.)
65c		Full Trip Hinge
65d		Quick Disconnects for Front Wing Cylinder
65e		Rear Mast Weldment – Including Slides, Cylinders, Mounting Brackets, No Tank
65f		Rear Mast H1059IP, RH assembly, CSS (Or Equal)
65g		Polymer Valve Box Cover, Black
66		Reversible Plow, Heavy Duty Trip Edge, 10 Degree
66a		OW3153TE9 Moldboard Reversible, HD Trip Edge, 10 Degree (Or Equal)
66b		Carbide Blade, 12" Punching, w/Steel Cover Blade (for 11')
67		Twin Cylinder (Cushion Valve) Power Reverse Push Frame
68		Brace Arms for OW3153TE9 (Pair) (Or Equal)
69		30 1/2" Push Swivel
70		Dead Sheave Leveling Device (Stainless Steel Cable)
71		Rubber Deflector, 12" wide, for Moldboard
72		132 WHD RH Wing Weldment, Standard RH Wing (Or Equal)
73		Carbide Blade, 12" Punching, w/Steel Cover Blade (for 132 Wing)
74		Full Trip Hydraulic Arms (Cushion Spring Lower)
75		Hook Lift Model SL-412 Swap Loader, 40,000# Lift Capacity (Or Equal)
76		Dump Body – Beau Roc Model DH14 w/Hook Lift Application, Black (Or Equal)
77		Downeaster Spreader Model DS9912 Stainless Steel, Hydraulic, Screens, Flip Chute, w/Hook Lift Application (Or Equal)
78		16' Beaver Tail Flat Bed Roll Off w/Hook Lift Application, Chain Racks, (8) Deck Mounted D-Rings
79		Headboard w/Cab Shield
80		LED ABL Heated Plow Lights
81		LED Strobes Front and Sides of Cab Shield
82		LED Strobes, S/T/T & B/U at Rear of Truck
83		LED Wing and Sander Light
84		LED Amber Light Mounted on Front of Plow Frame
85		Pintle Plate w/Hook and D-Rings, 7-Way Trailer Plug
86		US Electric Tarp System w/Cover (Or Equal)
87		(2) Cameras, 1-Wing, 1-Rear

88		On-Spots
89		Poly Fenders (Tandem), Mud Flaps w/Anti Sails
90		Hydraulics: A10 Rexroth Load Sense Pump w/Shut Off, Drive Shaft, Hyd.Tank, Hyd Oil, Hose Kit, Stainless Steel Lines Where Feasible
91		(6) Walvoil Valves
92		DEL Air Controls
93		Cirus EZ Spread 3 Spreader Controller
94		Divertor Valve
95		Liquid Spray System (2) 75 Gallon Calcium Tanks w/Electric Calcium Pump
96		24" x 24" External Tool Box (Mounted on Passenger Side)
WARRANTY ITEMS		
1		Extended Warranty Options including term and pricing
2		Allison 4000 RDS Series Transmission Extend Warranty, 7 Years/Unlimited Miles (Or Equal)
3		Axle: Front/Single Rear HD Moderate 7 Year/150,000 Mile Extended Axle Coverage. (Or Equal)
4		EW4: DD13 VOC 7 Years / 150,000 Miles Full Coverage, FEX Applies. (Or Equal)
5		TC4: HD MODERATE VOC 7 Years / 150,000 Miles Extended Truck Coverage, FEX Applies. (Or Equal)